

COMPACT LED EVO N 1200

LED GO!



220-240 V | LED |  |  | IP20 | IK07 |  CE

TECHNICAL PARAMETERS

Ingress protection:	IP20;
Impact resistance:	IK07;
Nominal power [W]:	25.00; 32.00; 44.00; 50.00; 58.00;
Luminous flux [lm]*:	2900 - 6800
Colour rendering index:	>80;
SDCM:	≤ 3;
Energy efficiency class:	A+;
Material of the body:	ABS;
Diffuser material:	PS; PC;
Diffuser type:	OPAL;
Mounting version:	surface; modular ceilings;
Dimensions [mm]:	1195/250/66;

*Tolerance +/- 10%

CHARACTERISTICS

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM): ≤3.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

COMPACT LED EVO N 1200

LED GO!

AVAILABLE TYPES

[Click >> index, to see details](#)

COMPACT LED EVO N 1200 25W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Emergency lighting [h]	DIMM DALI	Energy efficiency class	Index
25	3000	2900	OPAL				A+	>> 905605
25	4000	3150	OPAL		3		A+	>> 630347
25	3000	2900	OPAL		3		A+	>> 630354
25	3000	2900	OPAL	yes			A+	>> 630477
25	4000	3150	OPAL				A+	>> 905599

COMPACT LED EVO N 1200 32W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Emergency lighting [h]	DIMM DALI	Energy efficiency class	Index
32	3000	3550	OPAL				A+	>> 905568
32	4000	3850	OPAL				A+	>> 905551
32	4000	3850	OPAL		3		A+	>> 630323
32	3000	3550	OPAL		3		A+	>> 630330
32	4000	3850	OPAL	yes			A+	>> 630446
32	3000	3550	OPAL	yes			A+	>> 630453

COMPACT LED EVO N 1200 44W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Emergency lighting [h]	DIMM DALI	Energy efficiency class	Index
44	4000	5150	OPAL		3		A+	>> 630361
44	3000	4750	OPAL		3		A+	>> 630378
44	4000	5150	OPAL	yes			A+	>> 630484
44	3000	4750	OPAL	yes			A+	>> 630491
44	4000	5150	OPAL				A+	>> 905636
44	3000	4750	OPAL				A+	>> 905643
44	4000	5150	OPAL			yes	A+	>> 628962
44	3000	4750	OPAL			yes	A+	>> 628979

COMPACT LED EVO N 1200 50W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Emergency lighting [h]	DIMM DALI	Energy efficiency class	Index
50	3000	5450	OPAL				A+	>> 905933
50	4000	5950	OPAL				A+	>> 905926
50	4000	5950	OPAL		3		A+	>> 630408
50	3000	5450	OPAL		3		A+	>> 630415
50	4000	5950	OPAL	yes			A+	>> 630521
50	3000	5450	OPAL	yes			A+	>> 630538

COMPACT LED EVO N 1200 58W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Emergency lighting [h]	DIMM DALI	Energy efficiency class	Index
58	4000	6800	OPAL				A+	>> 905858
58	4000	6800	OPAL	yes			A+	>> 630507
58	3000	6250	OPAL	yes			A+	>> 630514
58	3000	6250	OPAL				A+	>> 905865
58	4000	6800	OPAL			yes	A+	>> 628986

COMPACT LED EVO N 1200

LED GO!

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Emergency lighting [h]	DIMM DALI	Energy efficiency class	Index
58	3000	6250	OPAL			yes	A+	>> 628993
58	4000	6600	OPAL	yes		yes	A+	>> 630583

*Tolerance +/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2019-12-12



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



86/2017